

LED Surface Spot Downlight *FC Series*

IP 20




FC 2001 W

Product Specification

Type	: FC 2001 W
Lamp	: Master LED
Beam Angel	: 20° / 30°
Material	: Die Casting Aluminium
Finishing Procces	: Powder Coating

Dimension (mm)



Equipment

Lamp	Light Output	Lamp Wattage	Module efficacy	Replaced Wattage	Color Temp	CRI	Lfe Time	Degre	Dimmable
	lm	W	lm/W	W	K	Ra	hrs	°	
Master LED	440	7	62	50	2700, 3000, 4000	90	40.000	15, 24, 36	Yes
Master LED	635	8	79	50	2700, 3000	80	40.000	24, 36	No
Master LED	240	4	60	35	2700, 3000	80	25.000	24, 36	No
Master LED	425	5.5	77	50	2700, 3000, 4000	80	25.000	24, 36	No

Ceiling Light *SK-SR*

IP 20



Circle




Square


Product Specification

Lamp	: TL-E 22W/54-765
Housing	: Mild Steel
Finishing	: Powder Coating
Cover	: High Quality Acrylic
Can Use Battery	

Dimension (mm)



Circle



Square

Type	D	H
SK - SR 500	300	75
SK - SR 501	390	98

Equipment

Lamp	Light Output	Lamp Wattage	System Efficacy	Color Temp	CRI	Life Time
	Lm	W	Lm/W	K	Ra	hrs
TL-E 22W/54-765	1050	22	48	6200	72	13.000