


Flood Light



Product Specification

- Housing : Aluminium Die - Casting Shaft
- Finishing : Electrostatical Polyester Powder Coating
- Diffuser : Protective Tempered Glass
- Reflector : Anodized Aluminium Reflector



| Type | Dimension (mm) | | |
|--------------|----------------|-----|-----|
| | W | L | H |
| SK WHALE 250 | 250 | 350 | 100 |
| SK WHALE 330 | 330 | 350 | 125 |
| SK WHALE 400 | 400 | 420 | 140 |

Equipment

| Model | Recommended Lamp | Lamp Holder | Capasitor | Ignitor | Ballast |
|--------------|-------------------|-------------|-----------------|---------|------------------|
| SK WHALE 250 | MHNT - D 70W/842 | Rx75 | Capasitor 12 uf | SN 58 | Magnetic Ballast |
| | CDMT - D70W/930 | Rx75 | Capasitor 12 uf | SN 58 | Magnetic Ballast |
| | CDMT - D 150W/930 | Rx75 | Capasitor 18 uf | SN 58 | Magnetic Ballast |
| | CDM -TD 150W/942 | Rx75 | Capasitor 18 uf | SN 58 | Magnetic Ballast |
| | CDMT - D 150W/832 | Rx75 | Capasitor 18 uf | SN 58 | Magnetic Ballast |
| SK WHALE 330 | SON-T 100W E40 | E40 | Capasitor 12 uf | SN 58 | Magnetic Ballast |
| | SON-T 150W E40 | E40 | Capasitor 18 uf | SN 58 | Magnetic Ballas |
| SK WHALE 400 | HPI-T 250W/745 BU | E40 | Capasitor 32 uf | SN 58 | Magnetic Ballast |
| | HPI-T 250W/745 BU | E40 | Capasitor 32 uf | SI51 | Magnetic Ballast |
| | HPI-T 400W/745 BU | E40 | Capasitor 50 uf | SI51 | Magnetic Ballast |
| | SON-T 250W | E40 | Capasitor 32 uf | SN 58 | Magnetic Ballast |
| | SON-T 400W | E40 | Capasitor 50 uf | SN 58 | Magnetic Ballast |

